

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **ICOBIT001**
Product name: **ICOPER-HP**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **LIQUID WATERPROOFING MEMBRANE**

1.3. Details of the supplier of the safety data sheet

Name: **Icobit Italia srl**
Full address: **via Vittorio Veneto, 54b**
District and Country: **00187 Roma (RM) Italia**
Tel.: **0871.58701**
Fax: **0871.562191**e-mail address of the competent person responsible for the Safety Data Sheet: **sds@icobititalia.com**

1.4. Emergency telephone number

For urgent inquiries refer to:
CAVp Osp. Pediatrico Bambino Gesù Roma Piazza Sant'Onofrio, 4 Cap 00165 Tel +3906 68593726
Az. Osp. Univ. Foggia Foggia V.le Luigi Pinto, 1 Cap 71122 Tel +390881-732326
Az. Osp. "A. Cardarelli" Napoli Via A. Cardarelli, 9 Tel 80131 +39081-7472870
CAV Policlinico "Umberto I" Roma V.le del Policlinico, 155 Cap 00161 Tel +3906-49978000
CAV Policlinico A. Gemelli Roma Largo Agostino Gemelli, 8 Cap 00168 Tel +3906-3054343
Az. Osp. Careggi U.O. Tossicologia Medica Firenze Largo Brambilla, 3 Cap 50134 Tel +39055-7947819
CAV Centro Nazionale di Informazione Tossicologica Pavia Via Salvatore Maugeri, 10 Cap 27100 tel +390382-24444
Osp. Niguarda Ca "Granda Milano Piazza Ospedale Maggiore, 3 Cap 20162 Tel +3902-66101029
Azienda Ospedaliera Papa Giovanni XXII Bergamo Piazza OMS, 1 Cap 24127 Tel +39800883300

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

SECTION 2. Hazards identification ... / >>

Hazard pictograms: --

Signal words: --

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
1,2-BENZISOTHIAZOLIN-3-ONE
May produce an allergic reaction.

Precautionary statements:

P501 Dispose of contents / container to in accordance with regulation
P273 Avoid release to the environment.

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 0,57
Limit value: 140,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ZINC OXIDE		
INDEX 030-013-00-7	0,099 \leq x < 0,11	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 215-222-5		
CAS 1314-13-2		
ETHANOLAMINE		
INDEX 603-030-00-8	0,019 \leq x < 0,03	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412
EC 205-483-3		STOT SE 3 H335: \geq 5%
CAS 141-43-5		LD50 Oral: 1089 mg/kg, ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
1,2-BENZISOTHIAZOLIN-3-ONE		
INDEX 613-088-00-6	0,009 \leq x < 0,02	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 220-120-9		Skin Sens. 1A H317: \geq 0,036%
CAS 2634-33-5		LD50 Oral: 450 mg/kg, LC50 Inhalation mists/powders: 0,21 mg/l/4h
TERBUTRINA		
INDEX	0,0025 \leq x < 0,013	Acute Tox. 4 H302, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100
EC 212-950-5		LD50 Oral: 1000 mg/kg
CAS 886-50-0		
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)		
INDEX 613-167-00-5	0 < x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to Annex VI to the CLP Regulation: B
EC		Skin Corr. 1C H314: \geq 0,6%, Skin Irrit. 2 H315: \geq 0,06% - < 0,6%, Skin Sens. 1A H317: \geq 0,0015%, Eye Dam. 1 H318: \geq 0,6%, Eye Irrit. 2 H319: \geq 0,06% - <

SECTION 3. Composition/information on ingredients ... / >>

CAS	55965-84-9		0,6% ATE Oral: 100 mg/kg, LD50 Dermal: 87,12 mg/kg, LC50 Inhalation mists/powders: 0,171 mg/l/4h
N,N-DIMETHYLACETAMIDE			
INDEX	616-011-00-4	0 < x < 0,01	Repr. 1B H360D, Acute Tox. 4 H312, Acute Tox. 4 H332
EC	204-826-4		ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS	127-19-5		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a agentes cancerígenos ou mutagénicos e procede à quarta alteração
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

SECTION 8. Exposure controls/personal protection ... / >>

CALCIUM CARBONATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	10				

TALC

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	2				RESP
WEL	GBR	1				RESP

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					3,6	2,16	3,16	2,16
					mg/m3	mg/m3	mg/m3	mg/m3

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	0,3		2,4		RESP Hinweis
VLA	ESP	10				
VLEP	FRA	10				
ПДК	RUS	10				a, φ
WEL	GBR	10				INHAL
WEL	GBR	4				RESP

ZINC OXIDE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	2		4		INHAL
MAK	DEU	0,1		0,4		RESP
VLA	ESP	2		10		
VLEP	FRA	5				
VLEP	FRA	10				RESP
ПДК	RUS	0,5		1,5		a

ETHANOLAMINE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,5	0,2	0,5	0,2	SKIN 11
MAK	DEU	0,51	0,2	0,51	0,2	
VLA	ESP	2,5	1	7,5	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
ПДК	RUS			0,5		n + a
WEL	GBR	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE

(3:1)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	0,2		0,4		INHAL

SECTION 8. Exposure controls/personal protection ... / >>

N,N-DIMETHYLACETAMIDE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	18	5	36	10	SKIN
MAK	DEU	18	5	36	10	SKIN
VLA	ESP	36	10	72	20	SKIN
VLEP	FRA	7,2	2	36	10	SKIN
VLEP	ITA	36	10	72	20	SKIN
VLE	PRT	36	10	72	20	SKIN
ПДК	RUS	1		3		n
WEL	GBR	36	10	72	20	SKIN
OEL	EU	36	10	72	20	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	pasty liquid	
Colour	various	
Odour	characteristic	
Odour threshold	not applicable	
Melting point / freezing point	not available	
Initial boiling point	100 °C	
Boiling range	100-105 °C	
Flammability	not applicable	
Lower explosive limit	not applicable	Temperature: 999 °C
Upper explosive limit	not applicable	Temperature: 999 °C
Flash point	not applicable	
Auto-ignition temperature	not applicable	
Decomposition temperature	not available	
pH	7,5-9,5	
Kinematic viscosity	not available	
Dynamic viscosity	10000-13000 mPas	
Solubility	partially miscible	

SECTION 9. Physical and chemical properties ... / >>

Partition coefficient: n-octanol/water	not applicable
Vapour pressure	not available
Density and/or relative density	1,29
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (130°C / 266°F)	72,00 %	
VOC (Directive 2004/42/EC) :	0,04 % - 0,57	g/litre
VOC (volatile carbon)	0,04 % - 0,45	g/litre
Explosive properties	not applicable	
Oxidising properties	not applicable	

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANOLAMINE

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANOLAMINE

Avoid exposure to: air, sources of heat.

10.5. Incompatible materials

ETHANOLAMINE

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

ETHANOLAMINE

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

SECTION 11. Toxicological information ... / >>

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: Not classified (no significant component)

ETHANOLAMINE

LD50 (Dermal): 2504 mg/kg
LD50 (Oral): 1089 mg/kg Rat
LC50 (Inhalation vapours): > 1,3 mg/l/6h Rat

1,2-BENZISOTHIAZOLIN-3-ONE

LD50 (Dermal): > 2000 mg/kg Rat
LD50 (Oral): 450 mg/kg Rat
LC50 (Inhalation mists/powders): 0,21 mg/l/4h

TERBUTRINA

LD50 (Dermal): > 2000 mg/kg RABBIT
LD50 (Oral): 1000 mg/kg RAT FEMALE
LC50 (Inhalation mists/powders): > 8 g/mc RAT

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LD50 (Dermal): 87,12 mg/kg Rabbit
LD50 (Oral): 457 mg/kg Rat
LC50 (Inhalation mists/powders): 0,171 mg/l/4h Rat

N,N-DIMETHYLACETAMIDE

LD50 (Dermal): 2100 mg/kg Rabbit
LD50 (Oral): 2820 mg/kg Rabbit
LC50 (Inhalation vapours): 8,8 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
1,2-BENZISOTHIAZOLIN-3-ONE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity**ZINC OXIDE**

LC50 - for Fish	1,1 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	1,7 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,14 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Fish	0,53 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,024 mg/l

ETHANOLAMINE

Chronic NOEC for Fish	1,2 mg/l <i>Oryzias latipes</i>
Chronic NOEC for Crustacea	0,85 mg/l <i>Daphnia magna</i>

1,2-BENZISOTHIAZOLIN-3-ONE

LC50 - for Fish	2,15 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	2,9 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,11 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Algae / Aquatic Plants	0,0403 mg/l <i>Pseudokirchneriella subcapitata</i>

TERBUTRINA

LC50 - for Fish	1,9 mg/l/96h (<i>Oncorhynchus mykiss</i>) (OECD 203)
EC50 - for Crustacea	6,4 mg/l/48h (<i>Daphnia magna</i>) (OECD 202)
EC50 - for Algae / Aquatic Plants	0,0067 mg/l/168h (<i>Desmodesmus subspicatus</i>) (OECD 201)
Chronic NOEC for Fish	0,073 mg/l (<i>pimephales promelas</i>) (OECD 210)
Chronic NOEC for Crustacea	0,05 mg/l (<i>Daphnia magna</i>) (OECD 211)
Chronic NOEC for Algae / Aquatic Plants	0,0005 mg/l (<i>Desmodesmus subspicatus</i>) (OECD 201)

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish	0,19 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	0,16 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,0052 mg/l/72h <i>Skeletonema costatum</i>
Chronic NOEC for Fish	0,02 mg/l <i>Danio rerio</i>
Chronic NOEC for Crustacea	0,1 mg/l <i>Daphnia magna</i>
Chronic NOEC for Algae / Aquatic Plants	0,00049 mg/l <i>Skeletonema costatum</i>

N,N-DIMETHYLACETAMIDE

LC50 - for Fish	> 500 mg/l/96h <i>Leuciscus idus</i>
EC50 - for Crustacea	> 500 mg/l/48h <i>Daphnia magna</i>

12.2. Persistence and degradability**ZINC OXIDE**

Solubility in water	2,9 mg/l
NOT rapidly degradable	

ETHANOLAMINE

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

SECTION 12. Ecological information ... / >>**1,2-BENZISOTHIAZOLIN-3-ONE**

Solubility in water 1288 mg/l

Rapidly degradable

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Solubility in water > 10000 mg/l

NOT rapidly degradable

N,N-DIMETHYLACETAMIDE

Rapidly degradable

12.3. Bioaccumulative potential**ZINC OXIDE**

BCF > 175

ETHANOLAMINE

Partition coefficient: n-octanol/water -2,3

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water 0,7

BCF 6,62

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Partition coefficient: n-octanol/water 0,75

BCF < 54

N,N-DIMETHYLACETAMIDE

Partition coefficient: n-octanol/water 0,969

12.4. Mobility in soil**ETHANOLAMINE**

Partition coefficient: soil/water -0,5646

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: soil/water 0,97

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 15. Regulatory information ... / >>

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H360D	May damage the unborn child.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization

SECTION 16. Other information ... / >>

- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for

SECTION 16. Other information ... / >>

evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 11 / 12 / 16.